

Propane Fuel

THERMADYNE

VICTOR_®

MATERIAL SAFETY DATA SHEET

HEMTREC Phone No. (800) 424 - 9300

Date Prepared: January 1, 1991
Date Revised: April 1, 2001

Form Number: 0056-1297
Core Part No: 0916-0004

Victor Equipment Company
P. O. Drawer 1007
Denton, Texas 76202

(940) 566 - 2000
Fax: (940) 381 - 1222

This MSDS is based on air/fuel or oxy/fuel process.
There may be other cautions for electric process.

Material Safety Data Sheet

SECTION I - MATERIAL IDENTIFICATION

Product Name: Liquefied Petroleum Gas or Propane (0916-0004)
Product Use: Heating Fuel

SECTION II - HAZARDOUS INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200)	OSHA PEL	ACGIH TLV	EXPOSURE LIMITS: 8 HR. TWA
Propane (CAS #74-98-6)	100 ppm	Not listed	

SECTION III - HAZARDS IDENTIFICATIONS

EMERGENCY OVERVIEW: Flammable gas. May cause flash fire or explosion. Contents under pressure. Harmful if inhaled.

POTENTIAL HEALTH EFFECTS:

INHALATION: May cause headaches and dizziness. May cause asphyxiation in high concentrations. Prolonged inhalation may be harmful.

EYE CONTACT: Direct contact with liquified gas can result in eye burns.

SKIN CONTACT: No hazard in normal industrial use.

INGESTION: Ingestion not likely, product is a gas at room temperature.

CHRONIC: Unknown.

CARCINOGENICITY: LISTED IN NTP? No IARC? No OSHA Regulated? No

SECTION IV - FIRST AID MEASURES

INHALATION: Remove to fresh air. If not breathing, give artificial respiration and/or give oxygen by trained personnel. Seek medical attention.

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention if

Propane Fuel

irritation persists.

SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: No emergency care anticipated.

SECTION V - FIRE FIGHTING MEASURES

Flashpoint (Method): -156°F (ND)
Flammable Limits: Lower: 2.3 Upper: 9.5
Autoignition Temperature: 874°F

GENERAL HAZARD: Flammable gas. Can readily form explosive mixtures at or above the flashpoint. Flashback along vapor trail possible.

FIRE FIGHTING INSTRUCTIONS: Evacuate area and fight fire from a safe distance. **DO NOT** extinguish a gas fire unless effective immediate shut-off of gas flow is possible. Explosive vapors could form. As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

EXTINGUISHING MEDIA: **DO NOT EXTINGUISH.** Use water to cool containers. Increase ventilation to prevent flammable air mixture.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, oxides of carbon.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources including internal combustion engines and power tools. Ventilate area. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Avoid breathing vapors. Avoid contact with eyes, skin, and clothing.

SECTION VII - HANDLING AND STORAGE

Use spark-proof tools and explosion proof equipment. Ground and bond containers when transferring material. Do not reuse this container. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Empty drums should be completely drained, properly sealed and promptly returned to a drum reconditioner, or disposed of properly. Keep away from heat, sparks and flame. Store in a cool dry place.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PROTECTIVE CLOTHING: Wear safety glasses with side shields (or goggles) and a face shield.

Propane Fuel

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: 7600 mmHg @ 80°C
Specific Gravity: 0.50
Solubility in Water: Negligible
pH: NA
Boiling Point: -44°F
Appearance & Odor: Colorless gas with no odor. If odorized, will have rotten egg odor.

Vapor Density (Air=1): 1.5
Evaporation Rate (n-Butyl Acetate=1): NA
Freezing Point: -306°F

SECTION X - STABILITY AND REACTIVITY

GENERAL: Stable

INCOMPATIBLE MATERIALS: Oxidizers

CONDITIONS TO AVOID: Heat, ignition sources.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI - TOXICOLOGICAL INFORMATION

No toxicity data determined.

SECTION XII - ECOLOGICAL INFORMATION

Not applicable.

SECTION XIII - DISPOSAL CONSIDERATIONS

Do not attempt to dispose waste or unused material. Return in container properly labeled, with valve protection cap in place to the supplier for proper disposal. Classification required before disposal. Material is classed as ignitable with a RCRA D001 hazardous waste number. Follow all federal, state and local requirements.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Liquefied Petroleum Gas, 2.1
HAZARD CLASS: Flammable gas (2.1)
IDENTIFICATION NUMBER: UN 1075
DOT Emergency Guide #: 22
Reportable Quantity (RQ): 2,000,000 pounds (Propane) in a single container.

SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act) All components are listed on the TSCA inventory.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act):
2,000,000 pounds. We recommend you contact local authorities for other reporting requirements.

SARA TITLE III (Superfund Amendments and Reauthorization Act):
311/312 Hazard Categories: Acute, Ignitable, Sudden Release of Pressure.

Propane Fuel

313 Reportable Ingredients: None

SECTION XVI - OTHER INFORMATION

PREPARED BY: TALEM, Inc. - Technical Services Division (817) 335 - 1186

FOOTNOTES:

NA - Not Applicable NE - Data Not Established CS - Cancer Suspect Agent OX - Oxidizer ND - No
Data Cor - Corrosive
CALC - Calculated EST - Estimated STEL - Short Term Exposure Limit TLV - Threshold Limit Value

PEL - Permissible Exposure Limit TWA - Time Weighted Average, 8 hours
THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED
IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO
SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN
PARTICULAR USE. NEITHER THE SELLER NOR PREPARER MAKES ANY WARRANTIES, EXPRESS OR IMPLIED,
CONCERNING THE INFORMATION PRESENTED.